



Spring-loaded D-ring stows against the body of the lantern when not in use



Large handle accommodates gloved hands



Flood light produces a soft, wide beam to illuminate your work area



Multi-function push-button switch; secondary rotary mode-selector switch



Hang over doors, pipes, ladder rungs, etc., for hands-free lighting

**Material/Lens** High impact polycarbonate housing. Rubberized lens cover. Available in yellow.

**Dims/Weight** Length: 6.75 in. (17.14 cm); Height: 6.5 in. (16.5 cm); Head Diameter: 3.55 in. (9.0 cm).  
Weight: 2.06 lbs (934 grams) with batteries; 1.41 lbs (640 grams) without batteries.

**Light Source/Output** C4® LED technology, impervious to shock with a 50,000 hour lifetime. High, Medium or Low output modes.

**Spot/Flood Combo –**

High - 1000 Lumens; 3 hour run time.  
Medium - 600 Lumens; 6 hour run time.  
Low - 75 Lumens; 55 hours run time.

**Spot –**

High - 750 Lumens; 75,000 candela; 548 meter beam distance; 3.5 hour runtime  
Medium - 500 Lumens; 45,000 candela; 426 meter beam distance; 6 hour run time  
Low - 35 Lumens; 3,200 candela; 113 meter beam distance; 125 hour run time

**Flood –**

High - 500 Lumens; 250 candela; 31 meter beam distance; 5 hour run time  
Medium - 230 Lumens; 120 candela; 22 meter beam distance; 12.5 hour run time  
Low - 25 Lumens; 10 candela; 6 meter beam distance; 170 hour run time

**Switch** Push button switch with momentary and click on operation. Using the momentary switch function, tap once for high, twice for medium and three times for low. The rotary switch behind the button selects the main/front beam, bottom/area light, or both for a combination of distance and path way lighting in one setting.

**Battery** Four “C” sized alkaline batteries. (not included with purchase)

**Features**

- LED Solid State Power Regulation provides maximum light output throughout battery life
- IPX7 rated design; waterproof to 1m, 2m impact resistance tested
- Integrated stand and D ring for hands-free lighting
- Floats

**Approvals** Meets applicable European Community directives.

**Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit [www.streamlight.com](http://www.streamlight.com) for full warranty information.

Item	UPC	Part #
Dualie Waypoint - Wrap - Yellow	080926-44940-4	44940
Dualie Waypoint - Box - Yellow	080926-44955--8	44955